


ALUMINIUM PROFILE S-LINE STANDARD



🇩🇪 S-LINE STANDARD

Für S-LINE STANDARD stehen zwei verschiedene Formen von Kunststoffabdeckungen zur Verfügung:

- plane Abdeckung
- halbrunde Abdeckung

Jede der zwei Formen ist in folgenden Varianten erhältlich:

- glasklar
- frost (halbkklar)
- milchig frost (opal)

Die plane Abdeckung (FLAT) ist auch als begehbare und bruchfeste Variante in glasklar, frost, milchig frost (opal) erhältlich.

LENS COVER 60°

Mit dem LENS COVER wird eine Bündelung und somit ein engerer Abstrahlwinkel erzeugt. Je nach Abstand zwischen FLEX STRIP und LENS COVER ist der Abstrahlwinkel max. 60°.

🇬🇧 S-LINE STANDARD

Two different shapes of plastic covers are available:

- flat cover
- round cover

Each of the two shapes are available in following versions:

- crystal clear
- frost (semitransparent)
- milky frost (opal)

The flat cover (FLAT) is also as a walkable and break-proof version in crystal clear, frost, milky frost (opal) available.

LENS COVER 60°

The LENS COVER provides a concentration of light rays and therefore a narrower beam angle. Depending on the distance between FLEX STRIP and LENS COVER the max. beam angle is 60°.

Produkttypen / Product Type

Artikel-Nr. order code	Bezeichnung description	Länge length
PRL691000	ALUMINIUM PROFILE S-LINE STANDARD	2 m
PRL691000X	ALUMINIUM PROFILE S-LINE STANDARD	3 m
PRL691000Y	ALUMINIUM PROFILE S-LINE STANDARD	5 m
PRL691000Z	ALUMINIUM PROFILE S-LINE STANDARD	lftm (max. 5 m)* / per meter (max. 5 m)*
PRL691000W	ALUMINIUM PROFILE S-LINE STANDARD weiß / white**	2 m
PRL691000WX	ALUMINIUM PROFILE S-LINE STANDARD weiß / white**	3 m
PRL691000B	ALUMINIUM PROFILE S-LINE STANDARD schwarz / black***	2 m
PRL691000BX	ALUMINIUM PROFILE S-LINE STANDARD schwarz / black***	3 m
PRL691S3E	ALUMINIUM END CAP FLAT S-LINE STANDARD	
PRL691S3EW	ALUMINIUM END CAP FLAT S-LINE STANDARD weiß / white**	
PRL691S3EB	ALUMINIUM END CAP FLAT S-LINE STANDARD schwarz / black***	
PRL691R2E	ALUMINIUM END CAP ROUND S-LINE STANDARD	
PRL691R2EW	ALUMINIUM END CAP ROUND S-LINE STANDARD weiß / white**	
PRL691R2EB	ALUMINIUM END CAP ROUND S-LINE STANDARD schwarz / black***	
PRL691L60E	ALUMINIUM END CAP LENS 60° S-LINE STANDARD	
PRL691L60EW	ALUMINIUM END CAP LENS 60° S-LINE STANDARD weiß / white**	
PRL691L60EB	ALUMINIUM END CAP LENS 60° S-LINE STANDARD schwarz / black***	




*Zuschnitt nach Maß / Custom Length

** weiß RAL 9016 / white RAL 9016 *** schwarz RAL 9005 / black RAL 9005

PLASTIC COVERS S-LINE

Formen shapes	Varianten versions
FLAT	CLEAR, FROST, MILKY (OPAL)
BREAK-PROOF FLAT	CLEAR, FROST, MILKY (OPAL)
ROUND	CLEAR, FROST, MILKY (OPAL)
LENS 60°	CLEAR

PLASTIC COVERS S-LINE



🇩🇪 S-LINE KUNSTSTOFFABDECKUNGEN

Für die S-LINE Profile stehen zwei verschiedene Formen von Kunststoffabdeckungen zur Verfügung:

- plane Abdeckung
- halbrunde Abdeckung

Jede der zwei Formen ist in folgenden Varianten erhältlich:

- glasklar
- frost (halbkklar)
- milchig frost (opal)

Die plane Abdeckung (FLAT) ist auch als begehbare und bruchfeste Variante in glasklar, frost, milchig frost (opal) erhältlich.

LENS COVER 60°

Mit dem LENS COVER wird eine Bündelung und somit ein engerer Abstrahlwinkel erzeugt. Je nach Abstand zwischen FLEX STRIP und LENS COVER ist der Abstrahlwinkel max. 60°.

🇬🇧 S-LINE PLASTIC COVERS

Two different shapes of plastic covers are available:

- flat cover
- round cover

Each of the two shapes are available in following versions:

- crystal clear
- frost (semitransparent)
- milky frost (opal)

The flat cover (FLAT) is also as a walkable and break-proof version in crystal clear, frost, milky frost (opal) available.

LENS COVER 60°

The LENS COVER provides a concentration of light rays and therefore a narrower beam angle. Depending on the distance between FLEX STRIP and LENS COVER the max. beam angle is 60°.



KOMPATIBILITÄT MIT PROFILEN COMPATIBILITY WITH PROFILES

S-LINE

	LOW	LOW 24	STANDARD	REC	CORNER	WALL	WALL SQUARE	WAVE	STEP UP	STEP DOWN	GLAS
PRL691S3C											
PRL691S3CX	×	×	×	×	×	×	×	×	×	×	×
PRL691S3CY											
PRL691S3CZ											
PRL691S3F											
PRL691S3FX	×	×	×	×	×	×	×	×	×	×	×
PRL691S3FY											
PRL691S3FZ											
PRL691S3M											
PRL691S3MX	×	×	×	×	×	×	×	×	×	×	×
PRL691S3MY											
PRL691S3MZ											
PRL691S3CB											
PRL691S3CBX	×	×	×	×	×	×	×	×	×	×	×
PRL691S3CBy											
PRL691S3CBZ											
PRL691S3FB											
PRL691S3FBX	×	×	×	×	×	×	×	×	×	×	×
PRL691S3FBy											
PRL691S3FBZ											
PRL691S3MB											
PRL691S3MBX	×	×	×	×	×	×	×	×	×	×	×
PRL691S3MBy											
PRL691S3MBZ											
PRL691R2C											
PRL691R2CX	×	×	×	×	×	-	-	-	-	-	-
PRL691R2CZ											
PRL691R2F											
PRL691R2FX	×	×	×	×	×	-	-	-	-	-	-
PRL691R2FZ											
PRL691R2M											
PRL691R2MX	×	×	×	×	×	-	-	-	-	-	-
PRL691R2MZ											
PRL691L60C											
PRL691L60CX	×	×	×	-	-	-	-	-	-	-	-
PRL691L60CZ											

Produkttypen / Product Type

Artikel-Nr. order code	Bezeichnung description	Länge length
PRL691S3C	PLASTIC COVER S-LINE FLAT CLEAR	2 m
PRL691S3CX	PLASTIC COVER S-LINE FLAT CLEAR	3 m
PRL691S3CY	PLASTIC COVER S-LINE FLAT CLEAR	5 m
PRL691S3CZ	PLASTIC COVER S-LINE FLAT CLEAR	lfm (max. 5 m)* / per meter (max. 5 m)*
PRL691S3F	PLASTIC COVER S-LINE FLAT FROST	2 m
PRL691S3FX	PLASTIC COVER S-LINE FLAT FROST	3 m
PRL691S3FY	PLASTIC COVER S-LINE FLAT FROST	5 m
PRL691S3FZ	PLASTIC COVER S-LINE FLAT FROST	lfm (max. 5 m)* / per meter (max. 5 m)*
PRL691S3M	PLASTIC COVER S-LINE FLAT MILKY (OPAL)	2 m
PRL691S3MX	PLASTIC COVER S-LINE FLAT MILKY (OPAL)	3 m
PRL691S3MY	PLASTIC COVER S-LINE FLAT MILKY (OPAL)	5 m
PRL691S3MZ	PLASTIC COVER S-LINE FLAT MILKY (OPAL)	lfm (max. 5 m)* / per meter (max. 5 m)*
PRL691S3CB	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION CLEAR	2 m
PRL691S3CBX	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION CLEAR	3 m
PRL691S3CBy	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION CLEAR	5 m
PRL691S3CBZ	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION CLEAR	lfm (max. 5 m)* / per meter (max. 5 m)*
PRL691S3FB	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION FROST	2 m
PRL691S3FBX	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION FROST	3 m
PRL691S3FBy	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION FROST	5 m
PRL691S3FBZ	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION FROST	lfm (max. 5 m)* / per meter (max. 5 m)*
PRL691S3MB	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION MILKY (OPAL)	2 m
PRL691S3MBX	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION MILKY (OPAL)	3 m
PRL691S3MBy	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION MILKY (OPAL)	5 m
PRL691S3MBZ	PLASTIC COVER S-LINE FLAT BREAK-PROOF VERSION MILKY (OPAL)	lfm (max. 5 m)* / per meter (max. 5 m)*
PRL691R2C	PLASTIC COVER S-LINE ROUND CLEAR	2 m
PRL691R2CX	PLASTIC COVER S-LINE ROUND CLEAR	3 m
PRL691R2CZ	PLASTIC COVER S-LINE ROUND CLEAR	lfm (max. 3 m)* / per meter (max. 3 m)*
PRL691R2F	PLASTIC COVER S-LINE ROUND FROST	2 m
PRL691R2FX	PLASTIC COVER S-LINE ROUND FROST	3 m
PRL691R2FZ	PLASTIC COVER S-LINE ROUND FROST	lfm (max. 3 m)* / per meter (max. 3 m)*
PRL691R2M	PLASTIC COVER S-LINE ROUND MILKY (OPAL)	2 m
PRL691R2MX	PLASTIC COVER S-LINE ROUND MILKY (OPAL)	3 m
PRL691R2MZ	PLASTIC COVER S-LINE ROUND MILKY (OPAL)	lfm (max. 3 m)* / per meter (max. 3 m)*
PRL691L60C	PLASTIC COVER S-LINE LENS 60° CLEAR	2 m
PRL691L60CX	PLASTIC COVER S-LINE LENS 60° CLEAR	3 m
PRL691L60CZ	PLASTIC COVER S-LINE LENS 60° CLEAR	lfm (max. 3 m)* / per meter (max. 3 m)*

*Zuschnitt nach Maß / Custom Length

LEaD LiGHT

Experts in LED

LEaD LIGHT GmbH

Hoogeweg 132
47623 Kevelaer

Tel.: +49 2832/975208-0
Fax: +49 2832/975208-88

Web: www.LEaD-LIGHT.de
Mail: info@LEaD-LIGHT.de